

File Dynamics 27-Apr-04 08:36		FS 10	BN 633 SL 2575/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3			
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s								
JC 0.40 FM 1.00 UM 1.00								
EA/C 30.3 Ks/ft UN KIPS:0.1 FR 20000 MB 30								
DL -41 UT -1 PK 1 TM-PEAK								
F1 500 F2 213 A1 999 A2 995								
TS 12 TB 8.0						E B PD: 11051 T1 9.4 2L/C 4.7	VA 1000 UE 1024	LP 0.00 ft LI 1.0
UMX= 3.1 FMX= 47 AMX= 100 EMX= 0.1 MEX= 92 FUP= 1.00								
ACCEPT SQ-OFF FL-OFF PR-OFF								
ACCELEROMETER CALIBRATION N.I.S.T. Traceable								
SERIAL NUMBER: 11051 CALIBRATION FACTOR: 995 6/4 PAK (*5000): DATE: 27 Apr. 04 PDA OPERATOR: D/pe								



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

<-AT:PIEZORESISTIVE

OP: fred [ver:4.05]

AT:PIEZOELECTRIC->