

File Dynamics 11-Oct-04 13:18		FS — 10	BN 1302 SL 2741/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s					
JC 0.40 FM 1.00 VM 1.00					
EA/C 30.3 Ks/ft UN KIPS*0.1 FR 20000 MB 30					
DL -44 UT -1 PK 1 TM-PEAK		TS 12 B PD: 11153-060 LP 0.00 ft TB 8.0 T1 9.1 2L/C 4.7 UA 1000 UE 1024 LI 1.0			

<input type="checkbox"/> ACCEPT <input type="checkbox"/> SQ-OFF <input type="checkbox"/> FL-OFF <input type="checkbox"/> PR-OFF		UMX= 3.8 FMX= 60 AMX= 100 EMX= 0.3 MEX= 117 FUP= 1.00
		ACCELEROMETER CALIBRATION N.I.S.T. Traceable SERIAL NUMBER: 11153 CALIBRATION FACTOR: 1020 GIV PAK (*3000): _____ DATE: 11-Oct-04 PDA OPERATOR: Fred Nusslein
contact Pile Dynamics USA with your questions tel USA - 216 - 831- 6131 fax USA - 216 - 831- 0916		←-AT:PIEZORESISTIVE OP: FRED [ver:4.05] [AT:PIEZOELECTRIC]-→