

File Dynamics 22-Apr-04 16:07		FS 10	BN 436 SL 2544/ 3440/ 99	PJ: PN: HOPBAR	TG F2 -- US A2 F2 3.3
LE 39.6 ft AR 1.7 in2 EM 30000 Ksi SP 0.492 K/ft3 WS 16810 ft/s WC 16862 ft/s					
JC 0.40 FM 1.00 UM 1.00					
EA/C 30.3 Ks/ft UN 141230 FR 20000 MB 30	DL -41 UT -1 PK 1 TM-PEAK				
F1 500 F2 213 A1 999 A2 1030	TS 12 TB 8.0	E B PD: 11054 T1 9.2 2L/C 4.7	UA 1000	VE 1024	LP 0.00 ft LI 1.0

ACCEPT SQ-OFF FL-OFF PR-OFF
 UMX= 4.1 FMX= 63 AMX= 100
 EMX= 0.2 MEX= 123 FUP= 0.99



contact Pile Dynamics USA
 with your questions
 tel USA - 216 - 831- 6131
 fax USA - 216 - 831- 0916

ACCELEROMETER CALIBRATION N.I.S.T. Traceable
 SERIAL NUMBER: 11054
 CALIBRATION FACTOR: 1030 61V
 PAK <#5000>: _____ DATE: 22-Apr-04
 PDA OPERATOR: Fred Iver

<-AT:PIEZORESISTIVE

OP: fred Iver:4.05]

[AT:PIEZOELECTRIC->