



Pile Dynamics, Inc.

Pile Integrity Tester (PIT-QV & PIT-QFV) Specifications

21-091

Physical

Size: 272 X 212 X 60 mm (10.7 x 8.3 x 2.4 in)

Weight: 2.04 Kg (4.5 lbs)

Sunlight readable VGA color display for any lighting conditions, resolution 800 x 600 pixels

Screen size: 21.3 cm (8.4")

Temperature Range: Operating: -20 to 40° C (-4 to 104° F); Storage: -30 to 65° C (-22 to 149° F)

Powered by Internal Battery (10-hour duration)

Electronic

Data Storage: Built in 256 GB drive

USB port for data retrieval

24-bit A/D converter

Analog Signal Frequency response: 22 KHz. (-3dB)

Sampling Digitizing frequency of > 1 MHz (net frequency after DSP > 32 KHz.)

Sampling Frequency accuracy within 0.01%

Sampling speed of 32 KHz – 118 KHz.

Windows 10 Operating System

Functional

One (PIT-QV) or two (PIT-QFV) channels of acceleration data acquisition

One (PIT-QV) or two (PIT-QFV) integrators of acceleration to velocity

PIT-QV accepts data from one traditional accelerometer

PIT-QFV accepts data from two traditional accelerometers or from one traditional accelerometer and one traditional instrumented hammer

Input of names and descriptions for each pile tested

Date and time stamps

Signal amplification capability, variable over time available record sizes: 1K, 2K, and 4K

Data can be averaged over a variable number of blows

FFT (Fast Fourier Transform) feature

Other

Includes licenses of PIT-W Standard and PIT-S

Soft carrying case

Full one-year warranty

Operates in English or Metric units

Technical manual provided in PDF form on a USB drive